



Desktop survey undertaken from google street view with imagery dated: July 2022

All traffic management shall comply with all current legislation and guidance including Chapter 8, Safety at Street Works and Road Works (A Code of Practice).

Pedestrian management to be installed and managed to suit site conditions in accordance with current legislation & codes of practice by the contractor unless otherwise stated.

All signage and road markings shall conform with the Traffic Signs Regulations and General Directions (TSRGD).

Sign locations are indicative only, exact location to be determined on site.

Suitably qualified operative to assess site to ensure the installation complies with all current legislation. Any issues and/or changes from the original design should be immediately reported to the relevant contracts manager/designer.

This design is only valid for 12 months from date of production and should be re-evaluated if installation is to take place after this period.

Key:	
	Works Area
	Closure
	Vehicular Diversion Route
	Ped Diversion Route
	Cone
	Datum Point
	Temporary Traffic Signal
	Stop & Go Board
	Temporary Ped Signal
	Existing Bus Stop
	Temporary Sign
	Pedestrian Barrier

Safety information:	
Min width of sideways safety zone (S)	1.2m
Min length of longways clearance (L)	60m
A429	

Site information:	
NSG	Fosse Way, Tredington
Local Authority	Warwickshire
USRN	38300800
Road Type	Single lane carriageway
Road Width	Varies
Works Location	X:425402 Y:242217
Surveyed	X: Bus Stop(s) X: Parked Vehicles X
Perm Signals	X: Controlled Crossing X: Cycle Lanes X

Chapter 8 details:

**Detail B**

Single/Dual carriageway 40mph or less - 450mm traffic cones.  
Single/Dual carriageway 50mph or more - 750mm traffic cones.  
Dual carriageway national speed limit - 750mm traffic cones.  
relaxation 3m.

Notes:  
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).  
2) 45° tapers have 1.2m spacing, no relaxations.  
3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

**Detail C1**

Single/Dual carriageway 40mph or less - 450mm traffic cones.  
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:  
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).  
2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).

**Detail C2**

Single carriageway 40mph or less - 450mm traffic cones.  
Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:  
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

Rev	Date	Comments	By	Chk

**Balfour Beatty**  
Living Places  
Working in Partnership with  
**traffix**

total traffic & event management solutions  
Old Arden Brickworks (Boreham) | Southall West Midlands | B92 0DY  
+44 (0)800 819 9001 | +44 (0)1875 442507  
info@traffixuk.com | www.traffixuk.com

Project title: Traffic Management	
Drawing title: Proposed Blank Route A429 Fosseway Tredington CV36 4GL	
Date: 09/06/2025	Scale: NTS
Drawn: MO	Checked: BN
Project Number: TPX MT3176	Drawing Number: 002

This drawing is copyright & the property of Traffic & must not be copied in whole or in part without their written permission. Copyright is reserved. ©  
This drawing must not be scaled.  
The Contractor is to report all discrepancies & errors to the Contract Manager prior to works commencing.

AWS signage installed at least 2 weeks prior to works commencing. Dates & durations to be confirmed.

