



Desktop survey undertaken from google street view with imagery dated: July 2022

All traffic management shall comply with all current legislation and guidance including Chapter 8, Safety at Street Works and Road Works (A Code of Practice)

Pedestrian management to be installed and managed to suit site conditions in accordance with current legislation & codes of practice by the contractor unless otherwise stated

All signage and road markings shall conform with the Traffic Signs Regulations and General Directions (TSRGD).

Sign locations are indicative only, exact location to be determined on site.

Suitably qualified operative to assess site to ensure the installation complies with all current legislation. Any issues and/or changes from the original design should be immediately reported to the relevant contracts manager/designer.

This design is only valid for 12 months from date of production and should be re-evaluated if installation is to take place after this period.

Size of signage:

Single carriageway permanent speed limit as shown below or less)	40	50	60 or more
400mm			
750mm			
900mm			

Key:			
Work Area			Temporary Traffic Signal
Closure			Stop & Go Board
Vehicle Diversion Route			Temporary Ped Signal
Ped Diversion Route			Existing Bus Stop
Cone			Temporary Sign
Drum Point			Pedestrian Barrier

Safety information:

Min width of sideways safety zone (S)	0.5m
Min length of baysways clearance (L)	0.5m
The Green	

Site information:

NSG	Tysoe Road, Radway
Local Authority	Warwickshire
USRN	36302147
Road Type	Single lane carriageway
Works Location	X:437254 Y:248294
Surveyed	<input checked="" type="checkbox"/> Bus Stop(s) <input checked="" type="checkbox"/> Parked Vehicles <input checked="" type="checkbox"/>
Perm Signals	<input checked="" type="checkbox"/> Controlled <input checked="" type="checkbox"/> Cycle Lanes <input checked="" type="checkbox"/>

Chapter 8 details:

<b>Detail B</b>	
Single/Dual carriageway 40mph or less - 450mm traffic cones.	
Single/Dual carriageway 50mph or more - 750mm traffic cones.	
Notes:	
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).	
2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).	
<b>Detail C2</b>	
Single carriageway 40mph or less - 450mm traffic cones.	
Single/Dual carriageway 50mph or more - 750mm traffic cones.	
Notes:	
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.	

Rev	Date	Comments	By	City
1				

**Balfour Beatty**  
Living Places  
Working in Partnership with  
**traffix**

total traffic & event management solutions  
Old Arden Brickworks | Biscanhill | Solihull | West Midlands | B82 0DY  
t: +44 (0)800 819 8001 | f: +44 (0)1915 442507  
info@traffix.co.uk | www.traffix.co.uk

Project title:

Traffic Management

Drawing title:	Proposed Blank Route
Drawing title:	Main Road
Drawing title:	Radway
Drawing title:	CV35 0UN
Date:	13/06/2025
Drawn:	NTS
MO:	BN
Project Number:	002
Revision:	

This drawing is copyright & the property of Traffic & must not be copied in whole or in part without the written permission. Copyright is reserved. © The Contractor is to report all discrepancies & errors to the Contract Manager prior to works commencing.