


All traffic management shall comply with all current legislation and guidance including Chapter 8, Safety at Street Works and Road Works (A Code of Practice).

All signage and road markings shall conform with the Traffic Signs Regulations and General Directions (TSRGD).

This design is only valid for 12 months from date of production and should be re-evaluated if installation is to take place after this period.

Safety information:	
Min width of sideways safety zone (s)	1.2m
Min length of longways clearance (L)	60m
Samboorne Lane	

Chapter 8 details:

- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
- 2) 45° lapers have 1.2m spacing, no relaxations.
- 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead lapers and the facing wall of lane changes.

Single/Dual carriageway 40mph or less - 450mm traffic cones.
Single/Dual carriageway 50mph or more - 750mm traffic cones

3

1000000

Balfour Beatty

Living Places

Working in Partnership with

traffix®

total traffic & event management solutions

Old Alden, Bickwakes | Bakershill | Solihull | West Midlands | B92 0DY
t +44 (0)800 819 8001 | f +44 (0)1925 442507
info@traffix.co.uk | www.traffix.co.uk

This drawing is copyright & the property of Traffix & must not be copied in whole or in part without their written permission. Copyright is reserved. ©
This drawing must not be scaled.
The Contractor is to report all discrepancies & errors to the Contract Manager prior to works commencing.